



All flanges will be drilled unless otherwise specified by purchaser.

P/No	DESCRIPTION of PART	N/off	MATERIAL	SPECIFICATION	REMARKS
01	BODY	01	GUN METAL	BS1400 LG2	
02	COVER JOINT	01	GUN METAL	BS1400 LG2	
03	COVER STUD / BOLT	01	STEEL		NON ASBESTOS
04	COVER STUD NUT	AS REQUIRED	STEEL		ZINC PLATED
05	GLAND	AS REQUIRED	STEEL		ZINC PLATED
06	GLAND PACKING	01	GUN METAL	BS1400 LG2	
07	GLAND STUD	AS REQUIRED	STEEL		NON ASBESTOS
08	GLAND STUD NUT	AS REQUIRED	STEEL		ZINC PLATED
09	DISC	01	GUN METAL	BS1400 LG2	
10	DISC STEM NUT	01	MANGANESE BRONZE	BS2874 CZ114	
11	STEM	01	MANGANESE BRONZE	BS2874 CZ114	
12	HANDWHEEL	01	CAST IRON		
13	HANDWHEEL NUT	01	STEEL		ZINC PLATED
14	HANDWHEEL NUT WASHER	01	STEEL		ZINC PLATED
15	IDENTIFICATION PLATE	01	ALUMINIUM		
16	O/S INDICATOR	01	MANGANESE BRONZE	BS2874 CZ114	
17	O/S INDICATOR SCREW	01	STEEL		
18	SEAT (INTEGRAL)	01	GUN METAL		

Nominal Bore	mm	15	20	25	32	40	50	65	80	100	125	150
Fin. Wt(kg)		1.2	1.8	2.5	3.5	4.5	6.5	9.5	13.5	19.5	27.5	37.5

End connections: — Inlet: — VARIES — Outlet: — VARIES
 Flange finish: — VARIES
 Standard: — CUSTOMER REQ Class/rating: — CL 150
 Maximum pressure/temperature rating: — 16 BAR@180 DegC
 Maximum test pressure: — Hydraulic Body = 24.0 bars
 (Non-shock) Hydraulic Seat = 17.6 bars
 Pneumatic Seat = 6.0 bars
 Special features: —
 O/S Indicator: — OPTIONAL

		LK Valves & Controls Ltd	
TITLE: GLOBE VALVE		DRG No: ASSY-GLF-SL-LG2	
DATE: 07/03/2000		BY: [Signature]	
Drawn: DG		Date: 07/03/13	
Scale: NTS		Verified: CJ	
Material: GUN METAL		Projection:	
Specification: BS1400 LG2		Copyright: — THIS DRAWING IS THE PROPERTY OF LK VALVES AND MAY NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS WITHOUT THE WRITTEN CONSENT OF LK VALVES.	
STATEMENT: — AS IT IS OUR POLICY TO CONTINUALLY IMPROVE OUR PRODUCTS WE RESERVE THE RIGHT TO MAKE CHANGES WITHOUT NOTICE.			